

Huth – Pack 88

Para-Aramid staple fibre with PTFE blocking agent and silicone free running-in lubricant



p [bar]	25	100	100
v [m/s]	20	2	-
t °C	-100 ... +250 (200*)		
pH	2 - 12		
g/cm ³	1.20		

*recommended practical limits

Main applications:

- Pumps
- Valves
- Agitators
- Blenders
- Kneading devices
- Gate valves
- Fittings
- Stern tubes

Characteristics:

- Volume and pressure stable packing
- High cross section density safe against penetration of crystallizing media
- Good value for money
- Good protection against wear, abrasives and/or hardening products
- Dense surface through high PTFE content and special yarn structure
- Good chemical resistance

Suitable for:

- Chemical, sugar, paper and pulp industries, sewage treatment
- Oplants, general service industries

Form of delivery:

This packing can be manufactured from 3 to 50 mm square as well as in intermediate, inch sizes and special measurements.

04 - 09 mm	on	1 kg Spool	Special length, pre-cut or die formed rings on request.
10 - 15 mm	on	2.5 kg Spool	
16 - 25 mm	on	5 kg Spool	

1 kg of packing of the following cross-sections is equivalent to displayed metre lengths:

[size]	04	05	06	07	08	09	10	12	13	14	15	16	18	19	20	22	25
[m]	52	33,3	23,1	17	13	9,2	8,3	5,8	5,2	4,3	3,7	3,3	2,6	2,3	2,1	1,7	1,3

All technical information and advice is based on our experience and will be given most conscientiously but without any liability. Indication and figures need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.